



HIGH PERFORMANCE
CONCRETE ADMIXTURE

Phone: (407) 484-2604
Fax: (407) 656-8603
Email: rakoon@att.net
Website: www.barrier-1.com
1901 Tumblewater Blvd.
Ocoee, Florida 34761

Manufacturer's Warranty

The Barrier-1 Inc. warrants its product the Barrier-1 Concrete Admixture to be free from material defects and that the product conforms to its current applicable specifications of stopping moisture migration from the concrete itself for a period of five years from the date of placement of concrete. This warranty is provided, if said product is installed according to and in compliance with the manufacturer's instructions and requirements including the use of an ASTM E1745-97(2004) Class A Vapor Barrier with a permeance of 0.01 US perms or less. In the event that there is a moisture complaint, Barrier-1 Inc. reserves the right to inspect and test any and all materials to determine the source of the problem. If damages occur to floor covering materials because of moisture vapor emission, Barrier-1 Inc. will repair the slab with a corrective sealer and replace or repair the floor covering materials with the same products. Barrier-1 Inc. makes no other warranty, expressed or implied and is not responsible for substandard concrete workmanship in finishing, cracks, control joints and expansion joints as a source of moisture migration or other types of concrete additives used. The sole and exclusive remedy of purchaser for any claim concerning this product, including, but not limited to, claims alleging breach of warranty, negligence, strict liability or otherwise, is the replacement of material to reseal the concrete slab and replacement or repair of damaged floor covering materials, at the sole option of the Barrier-1 Inc.. All claims concerning this product shall be submitted in writing within five years of placement of concrete. In no event shall Barrier-1 Inc. be liable for any special, incidental, consequential or punitive damages, including loss of profits and use.

Warranty is enforced upon Barrier-1 Inc. receiving the following information; Concrete mix design prior to placement of concrete, concrete truck batch tickets, field engineer evaluations and reports, confirmation of compliance with strict water to cementitious materials (w/cm) ratio guidelines by concrete supplier and installer.

Prior to installation of flooring, Barrier-1 will drill sample cores and/or procure 3" cylinders on all project slabs containing Barrier-1 Admixture. The sample cores will be sent to an independent laboratory and tested for permeability. The results will be provided as part of the warranty closeout documents. All accounts must be paid in full and within the terms of payment time frames prior to any warranty being issued or enforced.

Project Information:

Name:

Address:

City:

State:

Zip:

Effective Date: _____

General Contractor:

Name:

Address:

City:

State:

Zip:

Specified Area:

Barrier-1 Inc. Representative: _____ Date: _____