



Phone: 877.224.5850
Fax: 866-594-3490
Email: info@barrier-1.com
Website: www.barrier-1.com
2582 South Maguire Road
Suite 254
Ocoee, Florida 34761

Manufacturers' Warranty: Admixture

The Barrier-1 Inc. warrants its product the Barrier-1 High Performance Concrete Admixture to be free from material defects and that the product conforms to its current applicable specifications of stopping moisture migration from the concrete itself for a period of ten years from the date of placement of concrete. This warranty is provided, if said product is installed according to and in compliance with the manufacturer's instructions and requirements including the use of an ASTM E 1745-09 Class A Vapor Barrier maintaining a permeance of 0.01 US perms (grains/ft²*hr*inHg) or less after the required product conditioning specified in ASTM E 1745-09, installed following ASTM E 1643-98(2005) guidelines for all concrete slabs on ground, suspended concrete slabs do not require a vapor barrier. In the event there is a moisture vapor emission complaint, Barrier-1 Inc. reserves the right to inspect and test any and all materials to determine the source of the problem. The sole and exclusive remedy of purchaser for any claim concerning this product, including, but not limited to, claims alleging breach of warranty, negligence, strict liability or otherwise, is the placement of a topical moisture remediation material and the labor and materials, like the original installed products, required for the removal, replacement or repair of damaged floor covering materials, at the sole option of Barrier-1 Inc.. Barrier-1 recognizes that cracks, control joints and expansion joints are a source of moisture migration from the substrate of slabs placed on ground and warrants slabs on ground against moisture related flooring failures as long as an ASTM E 1745-09 Class A Vapor Barrier conforming to the above guidelines is utilized. Barrier-1 Inc. makes no other warranty, expressed or implied and is not responsible for substandard concrete workmanship in finishing. All claims concerning this product shall be submitted in writing within ten years of the warranty issue date. In no event shall Barrier-1 Inc. be liable for any special, incidental, consequential or punitive damages, including loss of profits and use.

Warranty is enforced upon Barrier-1 Inc. receiving the following information: concrete mix design prior to placement of concrete, confirmation of compliance with strict water to cementitious materials (w/cm) ratio guidelines by concrete supplier, and confirmation from concrete supplier that Barrier-1 was added in accordance with manufacturer's instructions and requirements.

Moisture testing of slabs containing Barrier-1 High Performance Concrete Admixture is not required for the Barrier - 1 manufacturer's warranty to be in effect when concrete is dosed according to Barrier-1's recommendations. This admixture is formulated to eliminate the route of moisture vapor emission through concrete and meets or exceeds all guidelines pertaining to moisture emission as established by the flooring industry. All accounts must be paid in full and within the terms of payments, prior to any warranty being issued or enforced.

Effective Date:

Project Information:

General Contractor:

Barrier-1 Inc. Representative:

Date: